



STAINLESS STEEL BODY MAXIMUM O.A.H. 117.00" FRONT IMPACT PROTECTION SIDE ROLL PROTECTION

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- 5/STL SCUFFPLATE ON EACH CAB DOOR JAMB
- MOUNTING BASES FOR ANTENNAS LOCATED PER SHOP ORDER
- KUSSMAUL 1200 BATTERY CHARGER LOCATED IN CREW CAB SEAT RISER
- BATTERY CHARGER INDICATOR LOCATED ON D.S. SEAT RISER WITH BRACKET
- PERIMETER SCENE LIGHTS LOCATED PER SHOP ORDER
- 5/STL PROTECTIVE GUARD FOR ALL ROLL-UP DOORS
- PIERCE L.E.D. COMPARTMENT DUAL LIGHT STRIPS LOCATED PER SHOP ORDER
- SHELF TRACKS IN COMPARTMENTS D1, D3, P1 & P3
- TWO ADJUSTABLE SHELVES (FULL DEPTH/FULL WIDTH) IN COMPARTMENTS D1, D3, P1 & P3
- AMOR LUMABAR L.E.D. H2O LIGHT STRIPS AT FRONT OF HOSEBED
- COMPARTMENT VENTILATION SYSTEM WITH TIMER
- CIRCUIT BREAKER PANEL IN COMPARTMENT D3
- STAINLESS STEEL FENDER CROWNS FRONT AND REAR
- PIERCE LOGO MUDFLAPS FRONT AND REAR
- AIR INLET WITH DISCONNECT COUPLING LOCATED IN D.S. STEP WELL
- 20A SHORELINE RECEPTACLE FOR KUSSMAUL BATTERY CHARGER LOCATED IN D.S. STEP WELL
- ALUMINUM 4-WAY ON REAR OF CAB
- ELECTRIC DOOR LOCKS ON CAB DOORS
- HANNAY ELECTRIC REWIND BOOSTER REEL MODEL EF34-23-24-12 IN COMPARTMENT R1 WITH CAPACITY FOR 150' OF 1.00" NIEDNER REELTEX BOOSTER HOSE AND 1.50" PIPING
- HUSKY 3 SINGLE AGENT FOAM SYSTEM
- ONE 15A, 120V 4-PLACE DUPLEX RECEPTACLE LOCATED IN CAB
- ONE 15A, 120V RECEPTACLE LOCATED IN COMPARTMENTS D1, D3, P1 & P3

CUSTOMER APPROVAL				Pierce MANUFACTURING INC.		JOB NO.	25664
APPROVED BY:						SCALE	DATE
DATE:						1:24	
			CHASSIS DATA	TITLE	1500-D-1000P W/20 GAL FOAM CELL, 152" PUMPER BODY	DRAWN BY	08MAR12
			MAKE	FOR	(2) XLYAS, HLR, LADDERS THRU TANK, DELUGE, GENERATOR	SHA	13FEB12
			MODEL		MARION FIRE DISTRICT	CHECKED BY	
			AX6710	DWG NO.	MARION, NEW YORK		
					25664AD	SHEET SIZE	SHEET NO.
						D	1 OF 1